

Single Row Angular Contact Ball Bearing

select	Inquiry	Bearing No.	Dimensions (Size)					Basic Load Rating kN		Limiting Speed r/min	Weight (kg)
			d	D	2B	r12	r34	Dynamic	Static	Grease Oil	
			(mm)	(mm)	(mm)	(mm)	(mm)				
7220ACM/DB	100	180	68	2.1	1.1	242	260	4600	6100	7.48	
7320ACM/DF	100	215	94	3	-	345	395	1900	2800	19.2	
7320BM/DF	100	215	94	3	-	305	355	1900	2800	16.8	
7320BT/DT	100	215	94	3	1.1	309	354	4100	5500	15.2	
7222CM/DB	110	200	76	2.1	1.1	299	342	4100	5500	10	
7222ACM/DB	110	200	76	2.1	1.1	286	325	2000	3000	9.84	
7222BM/DBCB	110	200	76	2.1	1.1	250	289	4000	6000	7.92	
7322ACM/DT	110	240	100	3	1.1	389	463	3700	5000	19.8	
7322ACM/DF	110	240	100	3	-	389	463	3700	5000	19.9	
7322BM/DB	110	240	100	3	1.1	347	425	3700	5000	22.9	
7322BM/DF	110	240	100	3	-	347	425	3700	5000	23.5	
7024AC/DF	120	180	56	2	-	164	214	4200	5600	4.62	
7024BM/DT	120	180	56	2	1	140	185	2000	2900		
7224ACQ5/DB	120	215	80	2.1	1.1	307	367	3800	5000	13.1	
7324AC/DF	120	260	110	3	-	400	540	3300	4500	27.4	
7324B/DT	120	260	110	3	1.1	410	525	3300	4500	29.2	
7226BM/DBCB	130	230	80	3	1.1	278	350	1800	2600	15.1	
7326B/DF	130	280	116	4	-	403	537	3000	4000	35.9	
7326B/DT	130	280	116	4	1.5	403	537	3000	4000	35.9	
7028AC/DF	140	210	66	2	-	203	275	3600	4800	6.92	
7228BM/DB	140	250	84	3	1.1	309	414	3200	4200	17.2	
7228BM/DBCB	140	250	84	3	1.1	310	415	1700	2300	17.2	
7328B/DT	140	300	124	4	1.5	447	616	2800	3800	42.3	
7328BA/DT	140	300	124	4	1.5	445	600	2900	3900	42.3	
7030BM/DB	150	225	70	2.1	1.1	213	294	1700	2300	9.61	
7230B/DF	150	270	90	3	-	310	430	1600	2000	22	

Single Row Angular Contact Ball Bearing

7330AC/DF	150	320	130	4	-	582	857	2600	3600	51.6
7330B/DF	150	320	130	4	-	582	856	2600	3600	52.3
7032BM/DB	160	240	76	2.1	1.1	225	315	3100	4100	12.6
7232B/DB	160	290	96	3	1.1	340	500	1400	1900	27.8