

## Double Direction Thrust Ball Bearing

select	Inquiry	Model Number	Principal Dimensions (Size)			Basic Load Rating kN		Fatigue load limit kN	Speed ratings r/min	Weight (kg)	
			d (mm)	D (mm)	H (mm)	Dynamic C	Static C0	PU	Reference		Limiting speed
			52202	10	32	22	15.9	25	1		7000
52204	15	40	26	21.2	37.5	1.4	4300	6000	0.15		
52205	20	47	28	26.5	50	1.86	3800	5300	0.22		
52305	20	52	34	34.5	60	2.24	3200	4500	0.33		
52406	20	70	52	70.2	122	4.5	2200	3200	1		
52206	25	52	29	24.7	46.5	1.86	3600	5000	0.25		
52306	25	60	38	35.8	65.5	2.4	2800	4000	0.47		
52407	25	80	59	76.1	137	5.1	2000	2800	1.45		
52207	30	62	34	35.1	73.5	2.7	3000	4300	0.41		
52208	30	68	36	44.2	96.5	3.6	2800	3800	0.55		
52307	30	68	44	49.4	96.5	3.55	2400	3400	0.68		
52308	30	78	49	61.8	122	4.5	2200	3000	1.05		
52408	30	90	65	95.6	183	6.8	1800	24	2.05		
52209	35	73	37	39	86.5	3.2	2600	3600	0.6		
52309	35	85	52	76.1	153	5.6	2000	2800	1.25		
52409	35	100	72	124	240	9	1600	2200	2.7		
52210	40	78	39	49.4	116	4.3	2400	3400	0.71		
52310	40	95	58	81.9	170	6.3	1800	2600	1.75		
52211	45	90	45	58.5	134	4.9	2200	3000	1.1		
52311	45	105	64	101	224	8.3	1600	2200	2.4		
52411	45	120	87	195	400	14.6	1300	1800	4.7		
52212	50	95	46	59.2	140	5.1	2000	2800	1.2		
52312	50	110	64	101	224	8.3	1600	2200	2.55		
52412M	50	130	93	199	430	16	1200	1700	6.35		
52213	55	100	47	60.5	150	5.5	2000	2800	1.35		

### Double Direction Thrust Ball Bearing

52214	55	105	47	62.4	160	5.85	1900	2600	1.5
52313	55	115	64	106	240	8.8	1600	2200	2.75
52314	55	125	72	135	320	11.8	1400	2000	3.65
52414M	55	250	107	234	550	19.3	800	1100	9.7
52215	60	110	47	63.7	170	6.2	1900	2600	1.55