

✖ 轴承型号	✖ 尺寸 dxDxB	✖ 额定载荷 (Cr) (Cor)		✖ 重量 (kg)	
29420/YA3	100x210x67	680	2000	10.5	
29422/YA3	110x230x73	840	2500	13.3	
29424	120x250x78	960	3000	19.4	
29424/YA3	120x250x78	960	3000	19.5	
29424J	120x250x78	960	3000	19.5	
29426/YA3	130x270x85	1050	3500	23	
29326/YA3	130x225x58	610	2050	8.26	
29328/YA3	140x240x60	675	2150	10.4	
29428/YA3	140x280x85	1250	3850	22.7	
29428J	140x280x85	1250	3850	22.7	
29330/YA3	150x250x60	750	2350	10.8	
29430/YA3	150x300x90	1280	4250	27.3	
29332/YA3	160x270x67	850	2800	14.3	
29432/YA3	160x320x95	1500	5000	33.3	
29334/YA3	170x280x67	880	2950	14.8	
29434/YA3	170x340x103	1650	5500	40.7	
29336/YA3	180x300x73	1000	3400	19.4	
29436/YA3	180x360x109	1800	6000	42.3	
29436J	180x360x109	1800	6000	42.3	
29338/YA3	190x320x78	1150	3850	23.1	
29438/YA3	190x380x115	2000	6500	60.1	
29340/YA3	200x340x85	1280	4500	28.5	
29440/YA3	200x400x122	2200	7500	69.2	
29244/YA3	220x300x48	484	910	7.92	
29348/YA3	240x380x85	1350	5200	35.5	
29448/YA3	240x440x122	2400	8150	74.5	

推力调心滚子轴承

29252M/YA3	260x360x60	798	1550	15.7	
29352	260x420x95	1700	6500	48.5	
29452	260x480x132	2650	9850	105	
29256	280x380x60	870	4000	19.1	