

双列角接触球轴承

✖ ✖											
轴承型号		外形尺寸					基本额定载荷		极限转速		重量
新型号	旧型号	d	D	B	rs □最小)	r2□最小)	动载	静载	脂	油	(kg)
3220X1D/W33	4086920/W33	100	170	60.3	2.1	1.1	132	191	1800	2900	7.8
3221X2DC	156721	105	190	79	2.1	1.1	173	240	1800	2900	10.6
3222X3DC	156822	110	170	56	2	1	120	154	1800	2900	4.9
4222X3D	86722	110	200	83	2.1	1.1	178	260	1800	2900	12
4024X2D	86124	120	180	56	2	1	120	182	1800	2900	6
4024D	4086124	120	180	60	2	1	110	183	1800	2900	6.1
4024X3D	4086124K	120	190	66	2	1	145	220	1800	2900	7.5
4024X3DC	156724	120	190	66	2	1.1	145	220	1800	2900	7.5
4024X3DC-1	156724K	120	215	80	2.1	1.1	200	293	1800	2900	13.2
4026X2D	4086726	130	200	75	2	1	142	235	1700	2300	9.1
4028X3D	86728	140	209.5	66	2	1	146	249	1700	2300	8.4
4028X3D/W33	156728/W33	140	209.5	66	2	1	146	249	1700	2300	8.4
4028D	4086128	140	210	69	2	1	146	249	1700	2300	8.8
4028DC	4156128	140	210	69	2	1	146	249	1700	2300	8.8
4030X3DC	156730K	150	210	56	2	1	111	197	1600	2000	6.3
4030X2D	86730	150	225	73	2.1	1.1	160	280	1600	2000	9.4
4030X2D/W33	86730/W33	150	225	73	2.1	1.1	160	280	1600	2000	9.4
4030X2DT	150	225	73	2.1	1.1	160	280	1600	2000	9.4	
4030D	4086130	150	225	75	2.1	1.1	160	280	1600	2000	9.6
4030X3D	86830	150	230	70	2.1	1.1	160	280	1600	2000	11.5
3230X2D/W33	150	270	90	3	1.1	225	405	1600	2000	23.3	
4932X2DC	156932	160	215	56	2	1	97	166	1600	2000	8.6
4932X3DC	156132K	160	239.8	76	2.1	1.1	191	340	1450	1850	12
3032X2D	3086132K	160	240	58	2.1	1.1	155	268	1450	1850	9.7
4032X2DC	156132	160	240	76	2.1	1.1	190	340	1450	1850	13.5
4032D	4086132	160	240	80	2.1	1.1	190	340	1450	1850	12

双列角接触球轴承

4032X3DC	156832	160	249.5	84	2.1	1.1	210	385	1450	1850	15
4934X3DC	156734	170	230	56	2	1	105	162	1450	1850	7
4034X3D	4086734	170	259.5	84	2	1	208	385	1300	1700	15
4034X2DC	156134	170	260	84	2.1	1.1	215	400	1300	1700	15